

High-end Supermarket Customized Lighting



^{Tel:} 8851 5998

HEADQUATER: Rm 505,No.2A Bldg, Skyworth Innovation Valley,Shiyan Street, Bao'An,Shenzhen,Guangdong,PR.C.

FACTORY: 4th-7th Floor, No.1 Building, Gangsui Industrial Zone, No.23 Shagang East Road, Gangkou, Zhongshan, Guangdong, P.R.C.

This in formation is for reference only and does not constit ute any form of commitment, products including but not limited to color, size, appearance and structure, please pre vail in kind. If there is any inconsistency between this in formation and the publicity, please prevail in kind without notice!

Lighting Series|Trunking Lighting System

Light Green International Co., Ltd

LIGHT GREEN

LIGHT GREEN / Speciali zed Professional Lighting Manufacturer

HIGHLIGHT PRODUCTS

INNOVATE TO CREATE

Special aesthetic lines and artisanal details To lock every inch light

Lighting Series | Trunking Lighting System

01 PRODUCT INSTRODUCTION

02 PRODUCT ADVANTAGE

WIRING-FREE
Modeling Splicing
Diversified Modules
High luminous efficiency/high power
Optical accessory

- **03** APPLICATION SITE
- **04** DATA SHEET

PRODUCTINTRODUCTION











PRODUCT INTRODUCTION

PRODUCT ADVANTAGE

MIRING-FREE
Modeling Splicing
Diversified Modules
High luminous efficiency/high power
Optical accessories

- APPLICATION SITE
- DATA SHEET

PRODCUT ADVANTAGE

WIRING-FREE
Modeling Splicing
Diversified Modules
High luminous efficiency/high power/optical accessory storage system

Bridge + Trac k 2 in 1 Wire-Free

The design of integrating bridge and wire channel is simple to install, it also reduce s the labor cost of installation and house

structural damage, so that the store as a whole is more neat and beautiful; press t ype dismantling lamps and lanterns, store layout can be changed freely.

To reduce the cost of labor

East to install

Clean and beautiful store


To reduce structural damage
 Easy to maintance

Freedom to change the layout











Modeling Splicing

Solutions














ENERGY SAVING 40%

High luminous efficiency 180lm/W



Ш

Optical Fittings Solutions

Multiple distribution RS/LS 20°, NW60°, WD 90°, DS 25°, one-row lens/two-row lens/PC cover, etc.

20° RS/LS Angele

60°


Narrow Angle

90°

25°

Wide Angle

Double Assymetric



01 PRODUCTS INSTRUCTION

02 PRODUCTS ADVANTAGE

WIRING-FREE Modeling Splicing Diversified Modules High luminous efficiency/high power Optical accessory

- **03** APPLICATION SITE
- **04** DATA SHEET

03

APPLICATION SITE

Food store

Supermarkets

Warehousing

Cosmetic Store

Auto Shop

Electric Stores

Electricores

Where we light?

Food store

Supermarkets

Warehousing

Cosmetic Store

Auto Shop

Electric Stores

Fashion Stores

DIY













SNACKS



COSMETIC



ELECTRIC

PRODUCT INSTRUCTION

PRODUCT ADVANTAGE

WIRING-FREE
Modeling Splicing
Diversified Modules
High luminous efficiency/high powe
Optical accessory

- APPLICATION SITE
- DATA SHEET

DATA SHEET



Model: F868 Trunking Lighting System

Beam angle: Narrow angle 60 °, Wide angle 90 °, RS/LS 20 °, DS 25 °, with 1-row and two-row lens.

RA:80

LENGTH	ССТ	POWER	LUMEN
7505454	20001/	2014/	2200184
750MM	3000K	20W	3200LM
	4000K	30W	4800LM
	6500K	40W	6400LM
		50W	8000LM
1500MM	3000K	30W	4800LM
	4000K	40W	6400LM
	6500K	50W	8000LM
		60W	9600LM
		60W	12000LM
		80W	12800LM



Model: F868 Trunking Rail

5-wire: L1, L2, L3, N, GND 8-wire: L1, L2, L3, N, GND, CHR, + 2 wires for Dimming/Emergency 12-wire: L1, L2, L3, N, GND, CHR, + 2 wires for Dimming/Emergency, +4 wires for emergency converter&Battery

		. Who is all effection of the about			
LENGTH	WIRES	TERMINAL BLOCKS	COLORS		
750MM	5-WIRE 5-WIRE 7-WIRE 7-WIRE	1PCS 2PCS 1PCS 2PCS	W/B		
1500MM	5-WIRE 5-WIRE 7-WIRE 7-WIRE 12-WIRE	1PCS 2PCS 1PCS 2PCS 2PCS	W/B		
3000MM	5-WIRE 5-WIRE 7-WIRE 7-WIRE 12-WIRE	2PCS 4PCS 2PCS 4PCS 4PCS	W/B		
4500MM	5-WIRE 5-WIRE 7-WIRE 7-WIRE 12-WIRE	3PCS 6PCS 3PCS 6PCS 6PCS	W/B		

Parameters of Modules

PICTURE	SIZE	POWER	DESCRIPTION
	SPOTLIGHT φ85*H1165MM	24W 30W 40W	Adjustable focal from 10° to 55 Adjustable up-down angle 0-90° Adjustable left-right angles from 0-350° Luminous efficiency up to 110-120lm/W
	PROJECTOR φ90*H215MM	60W	Rotate focus to adjust pattern sharpness Adjustable up-downangle 0-90° Adjustable left-right angles from 0-350° Logo can be customized
	DISPLAY L540*W160*H215MM	20W	Connect via WIFI P4 full color screen Cell phone APP control Content free editing
5	EMERGENCY SIGN		Customizable Languages

NORD CONNECTOR

PICTURE	WIRES	DESCRIPTION	COLOR
	5-WIRE 7-WIRE 12-WIRE	L-NODE CONNECTOR L/R Splicing Accessories 1 in 1 out	W/B
	5-WIRE 7-WIRE 12-WIRE	T-NODE CONNECOTR L/R Splicing Accessories 2 in 1 out	W/B
	5-WIRE 7-WIRE 12-WIRE	X-NODE CONNECT Splicing Accessories 2 in 2 out	W/B
	5-WIRE 7-WIRE 12-WIRE	Feed-in Box Splicing Accessories	W/B

Accessories

PICTURE	SIZE	NAME	DESCRIPTION
	1500MM 3000MM 4500MM	Hanging Wire Kits	Regular size is 1.5 meters Support other size customization Color: nickel plated
5 5	1500MM 3000MM 4500MM	Pendant Chain Kit	Regular size is 1.5 meters Support other size customization Color: nickel plated
	L64MM W35MM H15MM	Ceiling Kits	Color: nickel plated
	L200MM W65MM H29MM	Seamless Splicing Kits	Color: nickel plated
	L71MM W59MM H18MM	End Cap	W/B
	L1500MM	AC wire	5-wire*2.5mm² 7-wire*2.5mm² 12wire*2.5mm²
	L120MM	Female Connector	5-WIRE 7-WIRE 12-WIRE
	L120MM	Power Cord Connector Kit	5-WIRE 7-WIRE 12-WIRE
	L120MM	Feed-in Connector	5-WIRE 7-WIRE 12-WIRE

111

Accessories

111

PICTURE	SIZE	NAME	COLOR
	M20*1.5mm outlet 14mm	Cable Gland	W/B
	M20*1.5mm outlet 15.2mm	Conduit Gland	W/B